



Image Sensor	
Image sensor	1/2.7"color CMOS sensor
Lens	3.6mm, 2MP
Minimum illumination	Color: 0.01Lux@F1.2 (AGC ON) , 0 Lux IR ON
Audio	
Input/output	Built-in speaker 1.1W
Video	
Video compression	H.265+
Digital noise reduction	2D, 3D Noise reduction
Image frame rate	Max 15fps
Display resolution	1920*1080
Day and night mode	Dual filter adaptive intelligent switching
IR distance	15 meters

Network	
Wireless networks	2.4G WIFI(IEEE802.11b/g/n)
Ethernet	10/100Mbps
Protocols	TCP/IP、UDP/IP、DHCP、DNS、P2P
Interface protocol	ONVIF
IP address	Static IP address and dynamic IP address
Pan & Tilt	
Pan & Tilt	Horizontal: 355°, Vertical: 20°, Downward 90°
Alarm	
Alarm detection	Motion detection
Record	
Video storage	Micro SD card (max 128GB) local storage
Record type	Continuous recording, motion detection recording...
Interface	
Power	DC 5V/2A, 5W (with IR 7W)
Buttons	A reset button, Push to call
Ethernet interface	RJ45
Others	
Voice intercom	Two-way real time voice intercom
Push to call	Can be made manual for call to mobile phone
Environments	
Work temperature	-30° ~ 60°C
Work humidity	<95%RH
Specification	
Size (mm)	105*85mm
Weight	0.2kg (not include bracket)
Certificate	
Certificate	CE, ISO 9001, ISO 14001